

| | | | | |
|--|---|-------------------|--|---------------------------------|
| Outdoor Unit | Model of Outdoor Unit | | GWH18AGD-K6DNA1A/O | GWH09AGB-K6DNA1B/O |
| | Product Code of Outdoor Unit | | CB385W01900 | CB385W02300 |
| | Compressor Manufacturer/Trademark | | ZHUHAI LANDA COMPRESSOR CO., LTD | ZHUHAI LANDA COMPRESSOR CO.,LTD |
| | Compressor Model | | QXF-A120ZH190A | FTz-AN075ACBF-A |
| | Compressor Oil | | RB68EP | FW68DA |
| | Compressor Type | | Rotary | Rotary |
| | L.R.A. | A | 18.00 | 20.00 |
| | Compressor RLA | A | 5.00 | 3.00 |
| | Compressor Power Input | W | 1096 | 633 |
| | Overload Protector | | 1NT11L-6233 or HPC115/95U1 or KSD115°C | / |
| | Throttling Method | | Capillary | Capillary |
| | Operation Temp | °C | 16~30 | 16~30 |
| | Ambient Temp (Cooling) | °C | 18~43 | 18~43 |
| | Ambient Temp (Heating) | °C | -15~24 | -15~24 |
| | Condenser Form | | Aluminum Fin-copper Tube | Aluminum Fin-copper Tube |
| | Pipe Diameter | mm | Φ7 | Φ7 |
| | Rows-fin Gap | mm | 2-1.4 | 1-1.4 |
| | Coil Length (LXD _X W) | mm | 742X38.1X550 | 700X19.05X528 |
| | Fan Motor Speed | rpm | 900 | 900 |
| | Output of Fan Motor | W | 30 | 30 |
| | Fan Motor RLA | A | 0.40 | 0.40 |
| | Fan Motor Capacitor | μF | / | / |
| | Air Flow Volume of Outdoor Unit | m ³ /h | 2200 | 1950 |
| | Fan Type | | Axial-flow | Axial-flow |
| | Fan Diameter | mm | Φ438 | Φ400 |
| | Defrosting Method | | Automatic Defrosting | Automatic Defrosting |
| | Climate Type | | T1 | T1 |
| | Isolation | | I | I |
| | Moisture Protection | | IPX4 | IPX4 |
| | Permissible Excessive Operating Pressure for the Discharge Side | MPa | 4.3 | 4.3 |
| | Permissible Excessive Operating Pressure for the Suction Side | MPa | 2.5 | 2.5 |
| | Sound Pressure Level (H/M/L) | dB (A) | 52/-/- | 51/-/- |
| Sound Power Level (H/M/L) | dB (A) | 64/-/- | 62/-/- | |
| Dimension (WXHXD) | mm | 848X596X320 | 732X550X330 | |
| Dimension of Carton Box (LXWXH) | mm | 878X360X630 | 789X390X600 | |
| Dimension of Package (LXWXH) | mm | 881X363X645 | 792X393X615 | |
| Net Weight | kg | 33 | 25 | |
| Gross Weight | kg | 36 | 27.5 | |
| Refrigerant | | R32 | R32 | |
| Refrigerant Charge | kg | 0.75 | 0.53 | |
| Connection Pipe | Length | m | 5 | 5 |
| | Gas Additional Charge | g/m | 16 | 16 |
| | Outer Diameter Liquid Pipe | inch | 1/4 | 1/4 |
| | Outer Diameter Gas Pipe | inch | 3/8 | 3/8 |
| | Max Distance Height | m | 10 | 10 |
| | Max Distance Length | m | 25 | 15 |
| Note: The connection pipe applies metric diameter. | | | | |

The above data is subject to change without notice; please refer to the nameplate of the unit.